



Designed to integrate single and double glazed framing with a hinged door and fixed panel options with single glazed louvers with integrated screens.

Air-Flo Plus

The Air-Flo® Plus 125mm Framing system is purposely designed to provide a total solution for all residential and commercial applications, including fixed lights and hinged doors.

The Air-Flo® Plus 125mm Framing French Door is a 40mm wide panel consisting of a 85mm face as standard. An integrated barrier/ security door rebate allows for an overall frame size of 125mm.

Also integrable with the Swan Evo commercial panel to cater for larger panel sizes.









Suited towards the suburban housing and multi-unit residential market, the Air-Flo® Plus 125mm Framing system caters for timber reveals, various coupling, 4 point locking, screening solutions and a full range of glazing options up to 25mm double glazed.

Successfully tested for compliance with Australian Standards AS2047, achieving high acoustic and WERS energy ratings.

Specifying Air-Flo® Plus 125mm Framing ensures the client receives a solid, durable high performance product.

Typical Configurations











Key Features

- Framing options compatible with French/ Hinge door integration
- · A complete integrated screened frame offering external security and flyscreen options including Invisi-Gard®
- Suitable for suburban housing and multi-unit residential market
- Suitable to a range of terrain conditions
- · Various glazing options for energy compliance
- Integrated timber reveal provision to suite various construction types

Technical Specifications

Frame Dimensions	
Option 1	125 x 32mm
French Door Width	40mm

Maximum Product Perionii	ance
SLS (Pa)	1500
ULS (Pa)	2780
French Door Water (Pa)	200

3600mm Height Width 900mm French Door Height 2400mm French Door Width 1200mm French Door Weight 50kgs

Maximum Product Performance

Glazing Details	
Glass Position	Centre
Single Glazed	4 - 10.38mm
Double Glazed	18 - 25mm

Acoustic Performance Rw (C;Ctr) 6.38mm Laminate 30 (-1,-2) dB

Thermal Performance	
Uw range SG	3.1 – 5.9
SHGC range SG	0.17 - 0.58

Compatible Systems

Commercial Windows & Doors Swan Evo 45mm Commercial **Shopfront Door**

Commercial Windows & Doors Torrens 45mm Shopfront Door





customwindows.com.au

