



# The ideal solution for flush thresholds

# Altitude UltraFlat Weelchair Accessible Sliding Door

The Altitude UltraFlat Sliding Door has been specifically designed for projects where a AS1428.1 compliant flush sill is required. This UltraFlat sill option is perfect for aged care facilities, hospitals, learning environments and residential projects.


The door allows architects and designers the ability to achieve expansive openings without the need to compromise on performance or aesthetics.








## **Typical Configurations**





















#### **CAD Cross Section**

#### **UltraFlat**



#### **Key Features**

- Large sliding panels, ideal for high rise apartment and commercial applications
- Concealed drainage slots, high weather performance
- Internal sliding panel configurations
- Proprietary hardware, specially designed to accompany this product
- Fully interfaces with 76mm, 101.6mm and 150mm systems, allows for total design flexibility
- Accepts from 4mm to 12.4mm single glazed and up to 18mm double glazing units, allowing the designer to achieve the most demanding thermal and acoustic specifications
- AS1428.1 wheelchair compliant sill ideal for aged care living applications

### **Technical Specifications**

Frame Dimensions	
Option 1	101.6 x 46mm
Option 2	150 x 46mm

Maximum Recommended Sizes		
Height	2700mm	
Width	1500mm	
Weight	160kg	

Acoustic Performance	•
Glass Type	Rw (C; C <sub>tr</sub> )
6.38mm Laminate	32 (-2,-2)
10.5mm Hush Lam	36 (-0,-2)

Thermal Performance	
Uw range SG	4.2 - 6.0
SHGC range SG	0.30 - 0.69
Uw range DG	3.3 - 3.8
SHGC range DG	0.16 - 0.58

Glazing Details	
Single Glazed	4 - 12.4mm
Double Glazed	18mm

Compatible Systems
McArthur Evo Centre Pocket Framing
ecoFRAMEplus Centre Pocket Double Glazed Framing
Hunter Evo Flush Glazed Framing

















67 McDonald Cres, Bassendean WA 6054 Display 62, Homebase Subiaco, 55 Salvado Rd, Subiaco WA 6008





